Visage LED Block 1
VIS062
User Manual

Specification
1. **Weight: 4.9kg**
2. **Size: 460 x 200 x 125mm**
3. **Power input: AC 120V/240V, 60Hz/50Hz**
4. **Wattage: 34W**
5. **LEDS: 252PCS RGB (81 RED, 81 GREEN, 90 BLUE)**
6. **3PIN female XLR socket and 3PIN male XLR socket**
7. **Built-in microphone**

Mode	Dip10 Dip9	Dip8 Dip7 Dip6 Dip5 Dip4 Dip3 Dip2 Dip1	Function
Auto Run (Master projector)	0 0	X X 0 0 0 0 0 0	Colour changing and colour fading Select running speed via dip7, dip8
		0 0 X X X X X X	Static colour and flash Select static colour via dip1~dip3 (separately for R.G.B) select flash speed via Dip4~dip6
Sound acti-vated (Master projector)	0 1	X X X X X X X X	Change colour via sound activated
DMX	1 X	X X X X X X X X	DMX mode CH1 R CH2 G CH3 B CH4 Dimmer and flash
Other	1 0	0 0 0 0 0 0 0 1	DMX address is I when in DMX mode As Slave projector when in M/S mode
	1 0	0 0 0 0 0 0 0 0	Black out

CHANNEL	VALUE	FUNCTION
CH1	000-255	RED
CH2	000-255	GREEN
CH3	000-255	BLUE
CH4	000-189	DIMMER
	190-250	FLASH
	251-255	NO FUNCTION

- **Auto programs including colour change, fade, static and flash.**
- **Other control via DMX, optional dedicated controller (VIS062C), master/slave or sound activated.**

Distributed exclusively in the UK by:
Batmink Ltd, Beckery Road , Glastonbury, Somerset, BA6 9RX Tel: 01458 833186
www.batmink.co.uk